



| Technical data: | 1700 EX | 1700 EXB |
|------------------------|---------------|--------------|
| Max. working height | 16.80 m | |
| Max. outreach | 9.10 m | |
| Max. basket load | 200 kg | |
| Basket size | 1.25x0.8x1.1m | |
| Rotating basket | ± 50° | |
| Rotation | ± 400° | |
| Power supply | 230V/16A | 24V/200Ah/5h |
| Charger | | 24 V/30 A |
| Transport length | 6.25 m | |
| Transport height | 1.99 m | |
| Transport width | 1.66 m | |
| Operational width | 4.12 m | |
| Total weight | 2060 kg | 2200 kg |
| Controls | Proportional | |
| Hydraulic stabilizers | + | |
| Hydraulic propulsion | + | |
| 230 V outlet in basket | + | |

+ Standard

LARGE GROUND CLEARANCE



Up and over angle boom



Propulsion



Easy control



Large outreach

- 1700 EX is powered by an electric motor, connected to 230 V mains and is especially suitable where continuous operation is required. 1700 EXB is powered by a heavy duty battery pack, in total 24V/200 Ah/5h. Operation is possible independently of 230 V mains connection.
- The low centre of gravity provides a secure transport after the towing vehicle.
- The 1700 EX platforms are mounted with hydraulic propulsion, rotating basket and hydraulic stabilizers. Hydraulic propulsion enables the platform to propel itself around the work site. Operation from a special platform, giving a complete overview. The rotating basket makes it possible for 2 persons to operate parallel with e.g. a façade.
- The 1700 EX platforms are equipped with an unfolding scissor system, giving the lift an increased up and over outreach over high obstacles. When operating the scissor system up and down the basket will follow a vertical line. Furthermore the lift has no tail swing at rotation. Electric wiring to the basket is protected inside the telescopic boom. The telescopic cylinder is protected under the boom.
- The 1700 EX platforms are fitted with straightforward control, in the basket and at ground level. The hydraulic levers for the stabilizers are placed centrally on the chassis. The proportional controls ensure steady and smooth movements. The basket load of 200 kg applies in the complete working envelope.